

LEED® CONTRIBUTIONS

LEED® Submittal Form

Penetron Specialty Products presents the following LEED® certification table to meet your LEED-related, documentary requirements. For additional information, please contact your local sales representative or our Technical Support department at (631)941-9700.

Manufacturing Location: Allentown, Pennsylvania 18103

Guide to LEED® points:

MR 2.1: Divert construction and demolition debris from landfills and incinerators (50%)

MR 4.1: Reduce impact from extraction and processing of virgin materials. Use minimum 10% recycled Items (post consumer + 1/2 pre-consumer)

MR 4.2: Reduce impact from extraction and processing of virgin materials. Use minimum 20% recycled Items (post consumer + 1/2 pre-consumer)

MR 5.1: Increase demand for building materials and products that are extracted and manufactured within the region (10% Extracted, Processed Regionally)

MR 5.2: Increase demand for building materials and products that are extracted and manufactured within the region (20% Extracted, Processed Regionally)

EQ 4.1: Reduce the quantity of indoor air contaminants that are odorous, irritating, and/or harmful to the comfort and well-being of installers and occupants.

VOC Content	MR 2.1	MR 4.1	MR 4.2	MR 5.1	MR 5.2	EQ 4.1	Total Possible LEED® Points
Leveline 15	Premium Calcium Aluminate cement-based self-leveling underlayment						
< 5 g/L		✓	✓	✓	✓	✓	5
Leveline 45	Superior Calcium Aluminate cement-based self-leveling underlayment						
< 5 g/L		✓	✓	✓	✓	✓	5
Renew CR	Polymer-modified concrete resurfacer						
< 5 g/L		✓	✓	✓	✓	✓	5
Renew WS	Self-leveling, interior wearing surface						
< 5 g/L		✓	✓	✓	✓	✓	5
STX 50	Self-leveling primer for porous surface						
< 10 g/L				✓	✓	✓	3
STX 100	Self-leveling primer for porous and non-porous surfaces						
< 10 g/L				✓	✓	✓	3
SurFix FEP	High performance, cement-based, rapid-setting trowelable underlayment						
< 5 g/L		✓	✓	✓	✓	✓	5
SurFix SKM	Polymer-modified, rapid-setting, trowel-applied patching compound						
< 5 g/L		✓	✓	✓	✓	✓	5
VB 225	Moisture Vapor reduction system						
< 5 g/L	✓						1

